

Caster

6°
 8°
 10°
 12°

Steering

FRONT **REAR**

Tire: _____
 Wheel: _____
 Offset: +5

Front upright

0 mm
 0 mm
 0 mm

Front suspension

Combar: 3°
 Toe-in: 6°

92 mm
 143 mm
 2 mm

Ride height: 6 mm

Servo
 Battery

Rear suspension

Combar: 3°
 Toe-in: -2°

233 mm
 9 mm
 2 mm

0 mm
 0 mm

Ride height: 6 mm

Rear upright

Front Suspension mount Rollcenter

-2.0
 0.5 mm
 0 mm

Rear Suspension mount Rollcenter

-2.0
 0 mm
 +1.0
 0.5 mm

Front damper

Shock oil: #15
 Spring: 31 mm ϕ 11
 Spring color: Gold
 Piston: ϕ 12 mm
 Piston hole: 3

4 mm
 64.5 mm

Centered

Centered low gravity
 Centered upper motor

Rear damper

Shock oil: #15
 Spring: 31 mm ϕ 11
 Spring color: Purple/yellow
 Piston: ϕ 12 mm
 Piston hole: 3

6.5 mm
 64.5 mm

Spur Gear + Pinion Gear \times Reduction Gear = Gear ratio

80 T + _____ T \times 308 = _____

Motor & ESC: _____ Battery: _____
 Transceiver: _____ Gyro: _____ Sensitivity: _____

Rear diff

Spool
 Ball diff.

Alarm spool
 Alarm ball diff.

- 2nd Reduction Gear**
- 32T / 18T - 1.78
 - 34T / 18T - 1.89
 - 36T / 17T - 2.12
 - 40T / 16T - 2.50
 - 40T / 13T - 3.08
 - 42T / 11T - 3.82