

Caster

6°
 8°
 10°
 12°

Steering

FRONT **REAR**

Tire: _____
 Wheel: _____
 Offset: _____

Front upright

Front suspension

Combar: _____
 Toe-in: _____

Ride height: _____ mm ↑ GROUND

Servo
 Battery

Rear suspension

Combar: _____
 Toe-in: _____

Ride height: _____ mm ↓ GROUND

Rear upright

Front Suspension mount Rollcenter

Rear Suspension mount Rollcenter

Front damper

Shock oil: _____
 Spring: _____ mm
 Spring color: _____
 Piston: _____ mm
 Piston hole: _____

Centered

Centered low gravity
 Centered upper motor

Rear damper

Shock oil: _____
 Spring: _____ mm
 Spring color: _____
 Piston: _____ mm
 Piston hole: _____

Spur Gear + Pinion Gear × Reduction Gear = Gear ratio

_____ T + _____ T × _____ = _____

Motor & ESC: _____ Battery: _____

Transceiver: _____ Gyro: _____ Sensitivity: _____

Rear diff

Spool
 Ball diff.
 Alan spool
 Alan ball diff.

2nd Reduction Gear

- 32T / 18T - 1.78
- 34T / 18T - 1.89
- 36T / 17T - 2.12
- 40T / 16T - 2.50
- 40T / 13T - 3.08
- 42T / 11T - 3.82