



# Maxx® Slash® (Model 102076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

## Bearings & Bushings

5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)
5107A	Ball Bearing, black rubber sealed (17x26x5) (2)
5099A	Ball bearing, black rubber sealed (6x16x5mm) (2)
2728	Ball bearings (5x8x2.5mm) (2)
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)
5120A	Ball bearings, black rubber sealed (12x18x4mm) (2)
5101A	Ball bearings, black rubber sealed (12x21x5mm) (2)
5098A	Ball bearings, black rubber sealed (17x23x4mm) (2)
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)
5118A	Ball bearings, black rubber sealed (8x16x5mm) (2)
5101	Ball bearings, blue rubber sealed (12x21x5mm) (2)
7020	Ball bearings, blue rubber sealed (8x12x3.5mm) (2)

## Body & Accessories

10226	Body reinforcement set, black/ 3x10mm CS (8) (fits #10211 body)
10224	Body reinforcement set, black/ skid pads (roof)/ 3x10mm CS (14) (fits #10211 body)
10216	Body reinforcement set, front (left & right) (attaches to #10211 body)
10217	Body reinforcement set, rear (left & right) (attaches to #10211 body)
10213	Body support (fits #10211 body)
10219	Body support, side/ mount (left & right) (for #10211 body)
<b>10211</b>	<b>Body, Maxx Slash® (clear, requires painting)/ window masks/ decal sheet (includes body support, body plastics, latches, &amp; hardware for clipless mounting)</b>
<b>10211R</b>	<b>Body, Maxx Slash® (clear, requires painting)/ window masks/ decal sheet (includes body support, body plastics, latches, &amp; hardware for clipless mounting) (heavy duty)</b>
10211-BLUE	Body, Maxx Slash®, blue (painted)/ decal sheet (assembled with body support, body plastics, & latches for clipless mounting)
10211-GRN	Body, Maxx Slash®, green (painted)/ decal sheet (assembled with body support, body plastics, & latches for clipless mounting)
<b>10211X</b>	<b>Body, Maxx Slash®, ProGraphix® (graphics are printed, requires paint &amp; final color application)/ decal sheet (includes body support, body plastics, latches, &amp; hardware for clipless mounting)</b>
10211-RED	Body, Maxx Slash®, red (painted)/ decal sheet (assembled with body support, body plastics, & latches for clipless mounting)
10211-RNR	Body, Maxx Slash®, Rock n' Roll (painted)/ decal sheet (assembled with body support, body plastics, & latches for clipless mounting)
10218	Latch, body mount (4) (for clipless body mounting) (attaches to #10211 body)
10225	Skid pads (roof)/ retainers (2)/ 3x10mm CS (6) (fits #10211 body)

## Bumpers & Skidplates

10233	Bumper mount, front
10235	Bumper, front
10236	Bumper, rear
10245	Skidplate, center/ 4x30 CCS (4)/ 3x10 CS (4)
10244	Skidplate, front (1), rear (1)

## Chassis & Attachments

10215	Body mounts, front (left & right) (for clipless body mounting)
10214	Body mounts, rear (left & right) (for clipless body mounting)
10216	Body reinforcement set, front (left & right) (attaches to #10211 body)
10217	Body reinforcement set, rear (left & right) (attaches to #10211 body)
8924	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x10 CCS (3)
10233	Bumper mount, front
10235	Bumper, front
10236	Bumper, rear
10222	Chassis
8921	Chassis brace, front
8987	Covers, gear (2)
9627	Hold down, battery
10260	Motor mount cap
10223	Nerf bars, chassis (2)
9628	Retainer, battery hold-down (front and rear) (1 each)
8925	Seal kit, receiver box (includes o-ring, seal, and silicone grease)
8938	Shock tower, front (left & right halves)
8939	Shock tower, rear (left & right halves)
10245	Skidplate, center/ 4x30 CCS (4)/ 3x10 CS (4)
10244	Skidplate, front (1), rear (1)
<b>7799</b>	<b>Tires, rubber (2) (fits Traxxas® #7775X wheelie bar wheels)</b>
10278	Wheelie bar, assembled (fits Maxx® or Maxx Slash®)

7775	Wheels, wheelie bar (2)/ axles, wheelie bar (2)/ 10x15x4 plastic bushings (4) (for #7776, 8976, or 9576 wheelie bar)
<b>7775X</b>	<b>Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)</b>
<b>7775A</b>	<b>Wheels, wheelie bar, 6061-T6 aluminum (dark titanium-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)</b>
<b>7775G</b>	<b>Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)</b>
<b>7775T</b>	<b>Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)</b>
<b>7775R</b>	<b>Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)</b>

## Cush Drive Components

6465	Cush drive key/ pin/ elastomer damper
7793X	Housing, cush drive (front & rear halves)
<b>6442</b>	<b>Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)</b>
<b>6447R</b>	<b>Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)</b>
<b>6443</b>	<b>Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)</b>
6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
<b>6444</b>	<b>Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)</b>
<b>6449R</b>	<b>Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)</b>

## Differential Components

8981	Carrier, differential/ x-ring gasket/ o-ring (2)/ 10x19.5x0.5 TW
10280	Differential kit, center (complete) (20MM wt differential fluid) (fits Maxx®)
<b>10280X</b>	<b>Differential kit, center (complete) (aluminum carrier, 20MM wt differential fluid) (fits Maxx® or Maxx® Slash®)</b>
<b>10280A</b>	<b>Differential kit, center (complete) (aluminum carrier, 100K wt differential fluid) (fits Maxx® or Maxx® Slash®)</b>
<b>5136X</b>	<b>Differential oil kit (1 each: 10K, 30K, 50K weights)</b>
8949	Differential output yoke assembly, front or rear (assembled with external-splined half shaft)
10249	Differential output yoke assembly, front or rear, Maxx® Duty steel core (1) (assembled with external-splined half shaft)
8982	Gear set, differential (output gears (2)/ spider gears (4)/ spider gear shaft (2)/ output shaft (2)/ 2.5x13.8 pin (2))
8988	Gear, center differential, 44-tooth
5041	Grease, premium high performance (20cc)
8985	Input gear, transmission, 22-tooth/ 2.5x12mm pin
8986	Input shaft, transmission
<b>5130</b>	<b>Oil, differential (100K wt) (0.7 oz (20cc))</b>
<b>5135</b>	<b>Oil, differential (10K wt) (1.7 oz (50cc))</b>
5040	Oil, differential (20M wt) (standard)
<b>5136</b>	<b>Oil, differential (30K wt) (1.7 oz (50cc))</b>
5137	Oil, differential (50K wt) (1.7 oz (50cc))
8989	Output gear, center differential, hardened steel (2)
8978	Ring gear, differential/ pinion gear, differential (front)
8977	Ring gear, differential/ pinion gear, differential (rear)
8953	Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft)

## Driveline Components

<b>8952X</b>	<b>Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)</b>
<b>8952G</b>	<b>Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)</b>
8952	Carriers, stub axle (left & right)
<b>8952A</b>	<b>Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear) (2)</b>
<b>8952R</b>	<b>Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)</b>
10249	Differential output yoke assembly, front or rear, Maxx® Duty steel core (1) (assembled with external-splined half shaft)
<b>8951</b>	<b>Drive cup (1)/ 4x15.8mm screw pin (1) (for #8950X or 8996X steel CV drivshafts)</b>
8954	Drive hub, front (1)/ 3x10 screw pin (1)
10250	Driveshaft assembly, front or rear, Maxx® Duty steel core (left or right) (1) (fully assembled, ready to install)/ screw pin (1)
10255	Driveshaft, center, aluminum
<b>8950X</b>	<b>Driveshafts, steel constant-velocity (assembled), front or rear (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R required for a complete set)</b>

**Page 2 Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 102076-4) Parts List**

8983	Gear shaft, fixed/ driveshaft adapter (requires #8950X or 8996X steel constant-velocity driveshafts and #8984 transmission output gear)
8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)
8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
5040	Oil, differential (20M wt) (standard)
8953	Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft)
10253	Stub axle assembly, outer, Maxx® Duty (front or rear) (steel) (1)
8956	Wheel hubs, hex (2)/ 2.5x14 pins (2)
8956X	Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
8956G	Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4)
8956T	Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4)
8956R	Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4)
8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
8654A	Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4)
8654R	Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
10257	Wheel washers (4)
8957	Wheel washers (4)
8957X	Wheel washers, blue (4)
8957G	Wheel washers, green (4)
8957T	Wheel washers, orange (4)
8957R	Wheel washers, red (4)

**Front Suspension & Steering**

8926	Bulkhead tie bar, front, upper (1)/ lower (2) (steel)
8920	Bulkhead, front (upper and lower)
8932X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)
8932G	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)
8932A	Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)
8932R	Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4)
8932	Caster blocks (c-hubs), left & right
8916	Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)
8958	Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X)
8947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
8938X	Shock tower, front (left & right halves)
8946	Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
8937	Steering blocks, left & right
10230	Suspension arms, lower, black (left and right, front or rear) (2)
10230-BLUE	Suspension arms, lower, blue (left and right, front or rear) (2)
10230-GRN	Suspension arms, lower, green (left and right, front or rear) (2)
10230-ORNG	Suspension arms, lower, orange (left and right, front or rear) (2)
10230-RED	Suspension arms, lower, red (left and right, front or rear) (2)
8929	Suspension arms, upper, black (left or right, front or rear) (2)
8929X	Suspension arms, upper, blue (left or right, front or rear) (2)
8929G	Suspension arms, upper, green (left or right, front or rear) (2)
8929T	Suspension arms, upper, orange (left or right, front or rear) (2)
8929R	Suspension arms, upper, red (left or right, front or rear) (2)
8929A	Suspension arms, upper, white (left or right, front or rear) (2)
7743	Suspension pin retainer (4)
8940X	Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8)
8942	Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1)
8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)

8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)
8948X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
8948G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
8948A	Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
8948R	Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)

**Hardware**

1552	3x8mm Hex Cap Screws (6)/ Washers (6)/ Wrench (1)
3642	Attachment screws, shock (3x12mm shoulder screws) (6)
4859	CS 3x10 flathead (hex drive)
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX® 2.5, 2.5R, 3.3)
8447A	Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
8447X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)
8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)
3236	Screws, 2.5x12mm cap-head machine (6)
2577	Screws, 3x10mm button-head machine (hex drive) (6)
2587	Screws, 3x10mm caphead machine (6) (no washer)
2551	Screws, 3x10mm countersunk machine (6) (hex drive)
2578	Screws, 3x12mm button-head machine (hex drive) (6)
2579	Screws, 3x15mm button-head machine (hex drive) (6)
2553	Screws, 3x15mm countersunk machine (6) (hex drive)
3646	Screws, 3x15mm flat-head machine (hex drive) (6)
2583	Screws, 3x18 button-head machine (hex drive) (6)
2581	Screws, 3x25mm button-head machine (hex drive) (6)
2582	Screws, 3x30mm button-head machine (hex drive) (6)
2657	Screws, 3x8mm caphead machine (hex drive) (6)
2550	Screws, 3x8mm countersunk machine (6) (hex drive)
3936	Screws, 4x10mm button-head machine (hex drive) (6)
2535	Screws, 4x10mm countersunk machine (hex drive) (6)
3937	Screws, 4x12mm button-head machine (hex drive) (6)
3938	Screws, 4x14mm button-head machine (hex drive) (6)
3933	Screws, 4x16mm button-head machine (hex drive) (6)
2589	Screws, 4x20mm button-head machine (hex drive) (6)
2455	Screws, 4x24mm button-head machine (hex drive) (6)
2596	Screws, 4x25mm button-head machine (hex drive) (6)
2595	Screws, 4x35mm button-head machine (hex drive) (6)
8940X	Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8)
8942	Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1)
8943	Suspension pin set, rear (left or right) (hardened steel), 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1)

**Motors & Electronics**

7749	Adapter, standard servo (adapts standard servo to fit in X-Maxx®) Adapter, standard servo (adapts standard servo to fit in Maxx®, X-Maxx®, or XRT®)
8987	Covers, gear (2)
2092	Gear set (for 2090 servo)
10260	Motor mount cap
8960X	Motor mounts (front and rear)/ 4x10 BCS with split and flat washers (1)/ pin (1) (for installation of #3481 motor into Maxx®)
3483	Motor, 2000Kv 77mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink)
3483R	Rebuild kit, 2000Kv motor, brushless (includes plastic endbell, 5x16x5mm ball bearings (2), 5.05x7.5x.05 washer (1), 5.05x7.5x0.1 washer (1), 5.05x7.5x.19 washer (1), 6x5x8.5 spacer (1))
2091	Servo case/ gaskets (for 2090 waterproof servo)
8947X	Servo horn, steel
8947	Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
2090	Servo, digital high-torque (ball bearing), waterproof
2085	Servo, digital high-torque (ball bearing), waterproof

**Page 3 Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 102076-4) Parts List**

2085X	Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link
2085R	Servo, digital high-torque/high-speed, metal gear (ball bearing), waterproof
3484	Velineon® VXL-6s Brushless Power System, waterproof (includes VXL-6s ESC and 2000Kv, 77mm motor)
3485T	Velineon® VXL-6s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)

8952	Carriers, stub axle (left & right)
8952A	Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear) (2)
8952R	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)
8916	Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)
8958	Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X)

**Radio System, Batteries & Chargers**

2872X	5000mah 11.1v 3-Cell 25C LiPo Battery
2889X	5000mah 14.8v 4-Cell 25C LiPo Battery (long)
2857X	6400mah 11.1v 3-Cell 25C LiPo Battery
2914	AA 4PK
2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD® batteries to separate balance ports)
1926	Antenna caps, vinyl (2)/ antenna spool
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
1726A	Antenna, tube, black (1)/ vinyl antenna cap (1)/ wire retainer (1)
2943	Battery charge indicators, green (4), grey (4), blue (4)
6548	Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter)
8919X	Battery expansion kit (allows for installation of taller battery packs in Maxx® with standard chassis (329mm wheelbase))
2990	Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2))
2972	Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification
2973	Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification
2970	Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification
2981	Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification
6525	Communication link, telemetry expander
8527	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-battery 25.2 ESC to run on a single 14.8V battery pack)
2971	EZ-Peak Live 12-amp NiMH/LiPo Fast Charger with iD® Auto Battery Identification and Bluetooth®
2092	Gear set (for 2090 servo)
2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)
6535	Mount, temperature sensor (electric motors)/ wire tie/ thermal pad
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)
6552	Seal kit, expander box (includes o-ring, seals, and silicone grease)
6526	Sensor, auto-detectable, temperature
6527	Sensor, auto-detectable, voltage
6521	Sensor, temperature and voltage (long)
2091	Servo case/ gaskets (for 2090 waterproof servo)
2090	Servo, digital high-torque (ball bearing), waterproof
6553X	Telemetry Expander 2.0 and GPS module 2.0, TQi radio system
6550X	Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module)
6551X	Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)
6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)
6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)
6528	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-channel (transmitter only)
6529	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)
6530	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)
6511	Traxxas® Link Bluetooth® module

10234	Shock mount, lower (extended travel, left & right/ 3x18mm BCS (2)
8939X	Shock tower, rear (left & right halves)
10230	Suspension arms, lower, black (left and right, front or rear) (2)
10230-BLUE	Suspension arms, lower, blue (left and right, front or rear) (2)
10230-GRN	Suspension arms, lower, green (left and right, front or rear) (2)
10230-ORNG	Suspension arms, lower, orange (left and right, front or rear) (2)
10230-RED	Suspension arms, lower, red (left and right, front or rear) (2)
8929	Suspension arms, upper, black (left or right, front or rear) (2)
8929X	Suspension arms, upper, blue (left or right, front or rear) (2)
8929G	Suspension arms, upper, green (left or right, front or rear) (2)
8929T	Suspension arms, upper, orange (left or right, front or rear) (2)
8929R	Suspension arms, upper, red (left or right, front or rear) (2)
8929A	Suspension arms, upper, white (left or right, front or rear) (2)
7743	Suspension pin retainer (4)
8940X	Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (1), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8)
8943	Suspension pin set, rear (left or right) (hardened steel), 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1)
8941	Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
8940	Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)

**Shock Oil**

5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
5033	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
5029	Shock oil bottle (60cc) (for mixing shock oil)
5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack)
5038	Spinning carousel rack

**Shocks (GT-Maxx®)**

8965X	Body, GT-Maxx® shock (aluminum, blue-anodized) (1)
8965G	Body, GT-Maxx® shock (aluminum, green-anodized) (1)
8965T	Body, GT-Maxx® shock (aluminum, orange-anodized) (1)
8965R	Body, GT-Maxx® shock (aluminum, red-anodized) (1)
8962	Rebuild kit, GT-Maxx® shocks (lower cartridge, pistons, piston nuts, bladders, screws) (renews 2 shocks)
8964X	Shock caps, aluminum (blue-anodized), GT-Maxx®, shocks (4)
8964G	Shock caps, aluminum (green-anodized), GT-Maxx®, shocks (4)
8964T	Shock caps, aluminum (orange-anodized), GT-Maxx®, shocks (4)
8964R	Shock caps, aluminum (red-anodized), GT-Maxx®, shocks (4)
8964	Shock caps, GT-Maxx® shocks/ spring perch/ adjusters (2) (for 2 shocks)
8963	Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)/ rod ends (2)/ hollow balls (2)
8963T	Shock shaft, 72mm (GT-Maxx®) (TiN-coated) (2) (assembled with rod ends and steel hollow balls)
9660	Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o springs) (2)
8961G	Shocks, GT-Maxx®, aluminum (green-anodized) (fully assembled w/o springs) (2)
8961T	Shocks, GT-Maxx®, aluminum (orange-anodized) (fully assembled w/o springs) (2)
8961R	Shocks, GT-Maxx®, aluminum (red-anodized) (fully assembled w/o springs) (2)
8968X	Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968G	Spring retainer (adjuster), green-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968A	Spring retainer (adjuster), orange-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968R	Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
10240	Springs, shock (natural finish) (GT-Maxx®) (1.036 rate) (2)
10241	Springs, shock (natural finish) (GT-Maxx®) (1.150 rate, white stripe) (2)

**Ready-To-Race Model**

102076-4	Maxx® Slash®: 1/10 Scale 4WD Brushless Electric Short Course Racing Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®
----------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Rear Suspension**

8927	Bulkhead tie bar, rear, upper (1)/ lower front (1)/ lower rear (1) (steel)
8928	Bulkhead, rear (upper and lower)
8952X	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)
8952G	Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)

- 10242 Springs, shock (natural finish) (GT-Maxx®) (1.350 rate, brown stripe) (2)
- 10243 Springs, shock (natural finish) (GT-Maxx®) (1.400 rate, blue stripe) (2)

- 8948R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948 Toe links, molded composite, 100mm (89mm center to center) (black) (2)

**Spur Gears & Pinion Gears**

- 6487X Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6489X Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6490X Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6491X Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6491R Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6494X Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6495X Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6496X Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6492X Gear, 25-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
- 6497 Gear, 26-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
- 6442 Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
- 6447R Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
- 6443 Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
- 6448R Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
- 6444 Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
- 6449R Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)

**Steering Components**

- 7020 Ball bearings, blue rubber sealed (8x12x3.5mm) (2)
- 8947X Servo horn, steel
- 8947 Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
- 8946 Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
- 8948X Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948A Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948 Toe links, molded composite, 100mm (89mm center to center) (black) (2)

**Suspension Linkage**

- 8958 Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X)
- 7743 Suspension pin retainer (4)
- 8940X Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8)
- 8942 Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1)
- 8943 Suspension pin set, rear (left or right) (hardened steel), 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1)
- 8941 Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
- 8940 Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)
- 8948X Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948A Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)

**Team Traxxas Items**

- 2514 Decal sheet, racing sponsors
- 9950 Official Team Traxxas® racing decal set(flag logo/ 6-color)
- 9909 Traxxas® racing banner, red & black (3x7 feet)

**Tires & Wheels**

- 8447A Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
- 8447X Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)
- 8447G Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
- 8447R Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
- 8447 Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
- 5147X Nuts, 5mm flanged nylon locking (steel, serrated) (8)
- 10272 Tires & wheels, assembled, glued, left (1), right (1) (black wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated)
- 10272-BLK Tires & wheels, assembled, glued, left (1), right (1) (black with satin beadlock wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated)
- 10272-GRAY Tires & wheels, assembled, glued, left (1), right (1) (charcoal gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated)
- 10270 Tires, Maxx Slash® (belted) (2)/ foam inserts (2)
- 8956 Wheel hubs, hex (2)/ 2.5x14 pins (2)
- 8956X Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
- 8956G Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4)
- 8956T Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4)
- 8956R Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4)
- 8654 Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
- 8654G Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
- 8654A Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4)
- 8654R Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
- 8957 Wheel washers (4)
- 10257 Wheel washers (4)
- 8957X Wheel washers, blue (4)
- 8957G Wheel washers, green (4)
- 8957T Wheel washers, orange (4)
- 8957R Wheel washers, red (4)
- 10271 Wheels (black) (2)

**Transmission Components**

- 8987 Covers, gear (2)
- 8985 Input gear, transmission, 22-tooth/ 2.5x12mm pin
- 8986 Input shaft, transmission
- 5040 Oil, differential (20M wt) (standard)
- 8984 Output gear, transmission, 44-tooth (1) (requires #8950X or #896X steel constant-velocity driveshafts and #8983 driveshaft adapter)

**Traxxas Tools**

- 3433X Body reamer (aluminum handle)
- 3433 Body reamer (plastic handle)
- 3436 Cap, body reamer
- 3432 Scissors, curved tip
- 3431 Scissors, straight tip
- 8712 Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
- 8720 Speed bit handle, large (overmolded)
- 8721 Speed bit handle, medium (one piece)
- 8722 Speed bit handle, premium (rubber overmold)
- 8710 Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive

**Page 5 Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 102076-4) Parts List**

- 8711 Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
- 8719 Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
- 8716 Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
- 8716X Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm) 1/4" drive
- 8715 Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
- 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
- 8714 Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1 Phillips, and #2 Phillips bits), 1/4" drive
- 2748R Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
- 3415 Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm, 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle)

**Turnbuckles & Threaded Rods**

- 8948X Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948A Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948 Toe links, molded composite, 100mm (89mm center to center) (black) (2)

If you have questions or need technical assistance, call Traxxas at:

**1-888-TRAXXAS**

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

**TRAXXAS.COM**